



**JATCO, INC.**  
ENVIRONMENTAL  
PROTECTION  
EQUIPMENT

## **J-5000CX SPECIFICATIONS**

<b>Asme code vessel:</b>	<b>RATED 200 PSI</b>
<b>Operating Pressure:</b>	<b>40-100 PSI</b>
<b>Tank Capacity:</b>	<b>10 Gallon</b>
<b>Tank Length:</b>	<b>30"</b>
<b>Tank Diameter:</b>	<b>12"</b>
<b>Overall Height:</b>	<b>20"</b>
<b>Volume Capacity:</b>	<b>Up to 310 Gallons Per Hour</b>
<b>Inlet:</b>	<b>1" NPT</b>
<b>Outlet:</b>	<b>1" NPT</b>
<b>Relief Valve:</b>	<b>125 PSI</b>
<b>Check Valves/Brass:</b>	<b>300 PSI WOG</b>
<b>Internal Float Valve:</b>	<b>Stainless or Nytrophyl</b>
<b>Inlet Supply Pressure Conn:</b>	<b>1/4" Compression</b>
<b>All Seals:</b>	<b>Viton</b>



**JATCO, INC.**  
ENVIRONMENTAL  
PROTECTION  
EQUIPMENT

## **Stormwater Tank Model #J-7000**

### **SPECIFICATIONS**

Asme Code Vessel:	Rated 100 PSI
Operating Pressure:	40-100 PSI
Tank Capacity:	30 Gallon
Tank Length:	38"
Tank Diameter:	16"
Overall Height:	24 ¾"
Volume Capacity:	Up to 1400 gallons per hour
Inlet:	2" NPT
Outlet:	2" NPT
Relief Valve:	125 PSI
Check Valves/Brass:	200 PSI WOG
Internal Float Valve:	Nytrophyl or Stainless
Connector Tubing:	Stainless
Inlet Supply Pressure Conn.:	1/4" comp. stainless
All Seals:	Viton